Consent For Operation (CFO-Air,Water)	Karnataka State Pollution Control Board Parisara Bhavana,No.49, Church Street,Bengaluru-560001				
Consent No. AW-329465 Valid upto: 30/06/2026	Tele : 080-25589112/3, 25581383 Fax:080-25586321				
Industry Colour: RED Industry Scale: LARGE	email id: ho@kspcb.gov.in				
(This document contains 6 pages including annexure & excluding additional conditions)					
Combined Consent Order No. AW-329465	PCB ID: 10365 Date: 28/01/2022				
Combined consent for discharge of effluents under the Water (Prevention and Control of Pollution) Act , 1974 and emission under the Air (Prevention and Control of Pollution)Act , 1981					

Ref: 1. Application filed by the applicant/organization on 30/09/2021

2.Inspection of the
Industry/organization/by RO,on 25/10/20213.Proceedings of the ECM dated 01/01/2022
, held on 21/12/2021,held on 21/12/2021

Consent is hereby granted to the Occupier under Section 25(4) of the Water (Prevention & Control of Pollution) Act, 1974 (herein referred to as the Water Act) & Section 21 of Air (Prevention & Control of Pollution) Act, 1981, (herein referred to as the Air Act) and the Rules and Orders made there under and authorized the Occupier to operate /carryout industry/activity & to make discharge of the effluents & emissions confirming to the stipulated standards from the premises mentioned below and subject to the terms and conditions as detailed in the Schedule Annexed to this order.

Location:

Name of the Industry:	JSW Energy Ltd 860 MW Power Plant		
Address:	P.B. No.9, , Vidyanagara		
Industrial Area:	Not In I.A,	Toranagallu,	
Taluk:	Sanduru,	District: Bellary	
CONDITIONS:			

a) Discharge of effluents under the Water Act:

Sr	Water Code	WC(KLD)	WWG(KLD)	Remark
1	Cooling Water	49265.000	7613.000	Water is used for Cooling purposes and Treated in
				Recycling RO Plant and remaining taken to Guard pond and used for Ore
				Benefication Plant of JSW Steel Ltd.
2	Domestic Purpose	90.000	72.000	Water is used for domestic purposes and domestic sewage treated in STP, the treated water used for
				Greenbelt development.
3	Manufacturing Processes	612.000	281.000	Water is used for Process Boilers and Auxiliaries and effluents treated in Neutralization Plant and
				after used for ash conditioning purposes.

b) Discharge of Air emissions under the Air Act from the following stacks etc.

Sl. No. Description of chimney/outlet Limits specified refer schedule

The details of Sources, control equipments and its specification, type of fuel, constituents to be controlled in emissions etc. are detailed in Annexure-II.

The consent for operation is granted considering the following activities/Products;

Sr	Product Name	Applied Qty/Month	Unit
1	Electricity Generation Thermal Power 860MW/hr(2x130MW, 2x300MW)	627800.0000	MWH

This consent is valid for the period from01/07/2021to30/06/2026

To,

JSW Energy Ltd 860 MW Power Plant

COPY TO:

The Environmental Officer, KSPCB, Regional Office Bellary for information and necessary action.

- 2. Master Register.
- 3. Case file.

Traduced as advantation	ent For Operation	Karnataka State Pollution Parisara Bhavana		
	FO-Air,Water) sent No. AW-329465	Street,Be	engaluru-560001	
	lid upto: 30/06/2026		x:080-25586321	
Industry Colour: RED	Industry Scale: LARGE	email id: h	o@kspcb.gov.in	
(This document contains	6 pages including annexure & conditions)	c excluding additional	-	
	Consent Fee paid	: Rs. 2260000		
	SCHEDU	ULE		
	TERMS AND CON	DITIONS		
1. The discharge from t	the premises of the occupier shall	IS UNDER THE WATER ACT. Il pass through the terminal manho with the provisions of the Act/Rule	le/manholes where from	
	estic effluent shall be treated in s nk and soak pit shall be as per IS	eptic tank and with soak pit. No o S 2470 Part-I & Part-II.	verflow from the soak pit	
2(b). The treated sewag	ge effluent discharged shall conf	form to the standards specified in A	Annexure-I.	
3(a). The trade effluent g	generated in the industry shall be tre	eated in the ETP and treated effluent s	shall confirm to the	
standards stipulated by the				
3(b). The trade effluent sh	nall be handed over to CETP and m	naintain logbook of effluent generated	d & sent every day.	
4 The applicant shall :	notell flow measuring/nearding	devices to record the discharge of	antity and maintain the	
record.	nstall now measuring/recording	devices to record the discharge qu	iantity and maintain the	
	not change or alter either the qua without the previous consent/ p	lity or the quantity or the place of ermission of the Board.	discharge or temperature	
6. The applicant shall not allow the discharge from the other premises to mix with the discharge from his premises. Storm water shall not be allowed to mix with the effluents on the upstream of the terminal manhole where the flow measuring devices are installed.				
7 The daily quantity of	domestic effluent and trade efflu	tent from the industry shall not exc	eed the limits as	
indicated in this consent		icht from the medsury shan not ext	ceed the minits as	
	scharge the effluents only to the the premises is not permitted.	place mentioned in the Consent or	der and discharge of	
B. EMISSIONS:				
1. The discharge of emissions from the premises of the applicant shall pass through the air pollution control equipment and discharged through stacks/chimneys mentioned in Annexure-II where from the Board shall be free to collect the samples at any time in accordance with the provisions of the Act and Rules made there under. The tolerance limits of the constituents forming the emissions in each of the stacks shall not exceed the limits laid down in Annexure-II.				
2. The applicant shall provide port holes for sampling of emission, access platforms for carrying out stack sampling, electrical points and all other necessary arrangements including ladder as indicated in Annexure-II.				
3. The applicant shall upgrade/modify/replace the control equipment with prior permission of the Board.				
<u>C.MONITORING & H</u>				
1. The applicant shall get the samples of effluents & emissions collected and get them analyzed once a month/either by in house monitoring laboratory or through EP approved laboratories for the parameters as Indicated in Annexure I & II.				
	1000			

2. The applicant shall maintain log books to reflect the working condition of pollution control systems and also self monitoring results and keep it open for inspection.

D. SOLID WASTE (OTHER THAN HAZARDOUS WASTE) DISPOSAL:

1. The applicant shall segregate solid waste from Hazardous Waste, Municipal Solid Waste and store it properly till treatment/disposal without causing pollution to the surrounding Environment.

2. The solid waste generated shall be handled & disposed by scientific method without causing eye sore to the general public and to the surrounding environment.

ಕರ್ನಾಟಕ ರಾಜ್ಯ ಮಾರ್ದ್ಯ ನಿಯಂತ್ರಣ ಮಂಡಳ ಕರ್ನಾಟಕ	Consent For Operation (CFO-Air,Water)	Karnataka State Pollution Control Board Parisara Bhavana,No.49, Church Street,Bengaluru-560001
JP	Consent No. AW-329465 Valid upto: 30/06/2026	Tele : 080-25589112/3, 25581383 Fax:080-25586321
Industry Colour:	RED Industry Scale: LARGE	email id: ho@kspcb.gov.in

(This document contains

6 pages including annexure & excluding additional

E. NOISE POLLUTION CONTROL:

The applicant shall ensure that the ambient noise levels within its premises during construction and during operational period shall not exceed w.r.t Area/Zone as per Noise Pollution (Regulation and Control) Rules, 2000 as mentioned below:-

a) In Industrial Area 75 dB(A) Leq during day time and 70 dB(A) Leq during night time.

conditions)

- b) In Commercial Area 65 dB(A) Leq during day time and 55 dB(A) Leq during night time.
- c) In Residential Area 55 dB(A) Leq during day time and 45 dB(A) Leq during night time.
- d) In Silence Zone 50 dB(A) Leq during day time and 40 dB(A) Leq during night time.

Note: - * Day time shall mean 6 am to 10 pm and Night time shall mean 10 pm to 6 am.

- * dB(A) Leq denotes the time weighted average of the level of sound in decibels on scale A which is relatable to human hearing.
- * A "decibel" is a unit in which noise is measured.
- * "A", in dB(A) Leq, denotes the frequency weighting in the measurement of noise and corresponds to frequency response characteristics of the human ear.
- * Leq: It is an energy mean of the noise level over a specified period.

F. HAZARDOUS AND OTHER WASTES (MANAGEMENT & TRANSBOUDARY MOVEMENT)Rules 2016:

The applicant shall comply with the provisions of the Hazardous and other Wastes (Management & Transboundry Movement) Rules 2016.

G. GENERAL CONDITIONS:

1. The applicant shall not allow the discharge from the other premises to mix with the discharge from his premises.

- 2. The applicant shall promptly comply with all orders and instructions issued by the Board from time to time or any other officers of the Board duly authorized in this behalf.
- 3. The applicant shall set-up Environmental Cell comprising of qualified and competent personnel for complying with the conditions specified.

4. The Board reserves the right to review, impose additional conditions, revoke, change or alter terms and conditions of this consent.

5. The applicant shall forthwith keep the Board informed of any accidental discharge of emissions/effluents into the atmosphere in excess of the standards laid down by the Board. The applicant shall also take corrective steps to mitigate the impact.

6. The applicant shall provide alternate power supply sufficient to operate all Pollution control equipments.

7. The entire premises shall always be kept clean. The effluent holding area, inspection chambers, outlets, flow measuring points should made easily approachable.

8. The applicant shall display the consent granted in a prominent place for perusal of the inspecting officers of the Board.

9. The applicant his heirs, legal representatives or assignee shall have no claims what so ever to the continuation or renewal of this consent after expiry of the validity of consent.

Consent For Operation (CFO-Air,Water)	Karnataka State Pollution Control Board Parisara Bhavana,No.49, Church Street,Bengaluru-560001
Consent No. AW-329465 Valid upto: 30/06/2026	Tele : 080-25589112/3, 25581383 Fax:080-25586321
Industry Colour: RED Industry Scale: LARGE	email id: ho@kspcb.gov.in

(This document contains 6 pages including annexure & excluding additional conditions)

10. The applicant shall make an application for consent for subsequent period at least 45 days before expiry of this consent.

11. The applicant shall develop and maintain adequate green belt all around the periphery.

12. The applicant shall provide rain water harvesting system and shall provide proper storm water management system.

13. This consent is issued without prejudice to any Court Cases pending in any Hon'ble Court

14. The applicant shall furnish the Environmental statement for every financial year ending with 31st March in Form-V as per Environment (Protection) Rules, 1986. The statement shall be furnished before the end of September.

15. The applicant shall display flow diagram of the pollution control system near the pollution contol system/s.

NOTE:

The Conditions A (2b), (3b) mentioned in the schedule are not applicable.

Additional Conditions:

1. The occupier shall comply with all the additional terms and conditions stipulated in Annexures I, A & B attached here. 2. This consent order contains 11 pages including Annexures.



Consent For Operation (CFO-Air,Water)Karnataka State Pollution Control Board Parisara Bhavana,No.49, Church Street,Bengaluru-560001 Tele : 080-25589112/3, 25581383 Fax:080-25586321 email id: ho@kspcb.gov.inIndustry Colour: REDIndustry Scale: LARGE							Church u-560001 25581383 25586321	
(This	documen	t contains		es including annexure &	excluding ac	lditional		
Chi m.N o.	Chimne y attached to	KVA	Minimum chimney height to be provided above ground level (in Mts)	litions) Constituents to be controlled in the emission	Tolerance limits mg/NM3	Fuel	Control	Date of which air pollution control equipments shall be provided to achieve the stipulated tolerance limits and chimney heights conforming to stipulated heights.
			250		6		1	norginust
1	D.G. Sets	DG Set- 750 KVA cap for 300 MW- Unit-II	13	PM(mg/NM3),SO2 (PPM),NOx(PPM)	0,0,0	DIE	AEC	Before commissioning.
2	D.G. Sets	DG Set- 750 KVA cap for 300 MW- Unit-I	13	PM(mg/NM3),SO2 (PPM),NOx(PPM)	0,0,0	DIE	AEC	Before commissioning.
3	D.G. Sets	DG Set- 350 KVA cap for 130 MW- Unit-II	13	PM(mg/NM3),SO2 (PPM),NOx(PPM)	0,0,0	DIE	AEC	Before commissioning.
4	D.G. Sets	DG Set- 350 KVA cap for 130 MW- Unit-I	13	PM(mg/NM3),SO2 (PPM),NOx(PPM)	0,0,0	DIE	AEC	Before commissioning.
5	Boiler	1015TP Hx2 (Commo n	275	PM(mg/NM3),SO2 (PPM),NOx(PPM)	100,0,0	COA	ESP	Before commissioning.
		chimney 2x300 MW Coal& by product/ waste mixed Gas)						
6	Boiler	Boiler- 415TPH (130 MW Coal& by product/ waste mixed Gas)	115	PM(mg/NM3),SO2 (PPM),NOx(PPM)	100,0,0	COA	ESP	Before commissioning.
7	Boiler	Boiler- 415TPH (130 MW Coal& by product /waste mixed Gas)	115	PM(mg/NM3),SO2 (PPM),NOx(PPM)	100,0,0	COA	ESP	Before commissioning.

Note:

AEC : Accoustic Enclosures

ESP : E.S.P

Note:

1. The Noise levels within the premises shall not exceed 75 dB (A) leq during day time and 70 dB(A) leq during night time respectively.

2. The DG set shall be provided with acoustic measures as per SI.No.94 in Schedule-I of Environment (Protection)Rules.

3. There shall be no smell or odour nuisance from the industry.

Consent For Operation (CFO-Air,Water) Consent No. AW-329465 Valid upto: 30/06/2026	Karnataka State Pollution Control Board Parisara Bhavana,No.49, Church Street,Bengaluru-560001 Tele : 080-25589112/3, 25581383 Fax:080-25586321
Industry Colour: RED Industry Scale: LARGE	email id: ho@kspcb.gov.in
(This document contains 6 pages including ann conditions)	exure & excluding additional

LOCATION OF SAMPLING PORTHOLES, PLATFORMS, ELECTRICAL OUTLET.

1. Location of Portholes and approach platform:

Portholes shall be provided for all chimneys, stacks and other sources of emission. These shall serve as the sampling points. The sampling point should be located at a distance equal to atleast eight times the stack or duct diameters downstream and two diameters upstream from source of low disturbance such as a Bend, Expansion, Construction Valve, Fitting or Visible Flame for rectangular stacks, the equivalent diameter can be calculated from the following equation.

Equivalent Diameter = 2 (Length x Width) (Length + Width)

- 2. The diameter of the sampling port should not be less than 100 mm dia". Arrangements should be made so that the porthole is closed firmly during the non sampling period
- 3. An easily accessible platform to accommodate 3 to 4 persons to conveniently monitor the stack emission from the portholes shall be provided. Arrangements for an Electric Outlet Point of 230 V 15 A with suitable switch control and 3 Pin Point shall be provided at the Porthole location.
- 4. The ladder shall be provided with adequate safety features so as to approach the monitoring location with ease.

Signature Not Verified Digitally signed by Date: 2022.01.26 13:46:47 +05:30

For and on behalf of the Karnataka State Pollution Control Board