

Proposal
For
Sleeve Wrapper with
Shrink Tunnel Machine
By,



TAUREAN PAC



TAUREAN PAC

Office & Factory : 92-C, E.B. ROAD,
Sidco Industrial Estate,
Ambattur, Chennai - 600 098.
+91-44-4303 9318, 4864 4030
Email : info@taureanpac.com
www.taureanpac.com

To,

M/s. Forace Industries Pvt. Ltd,
PLOT NO. 40, SECTOR-11, SIDCUL,
Haridwar-249401 (U.K) INDIA
Mobile: +91-9690002696;
Email: material@foracepolymers.in

Kind attention : Mr. Ashwani Gupta
Sub: Offer for Sleeve Wrapper & Shrink Tunnel Machine
Ref: Your enquiry & discussion with Mr.Vikram
Quotation no: TP/Q/VV/226 -2020-21 dated 21st July, 2021

Dear Sir,
Greetings to you!

We are very much pleased to submit herewith our offer for Continuous motion sleeve wrapper with shrink tunnel

Offer No:01

4-Side Sleeve Wrapper with Shrink Tunnel

Suitable for LDPE shrink film 80-120 Microns thickness film.

The system consists of 2 units:-

1. Wrapping unit with front end sealing and side sealing unit
2. Heavy duty shrink tunnel

The product to be packed must be fed in the wrapper, for wrapping the tray with shrink film. It will sealed and wrapped with the shrink film, and then the product moves into the shrink tunnel for shrinking.

Technical Details of the Machine:-

Sleeve Wrapper

Model: AW-1200-V with side seal AW-600-H

Sealing Length: 1200mm Front end sealing

Sealing Length: 600mm Side Seal

Sealing Blade will be coated with Teflon coating

Air-cooling system after sealing

Seal and cut facility suitable for LDPE material
Pneumatically operated sealing system
Air Pressure req. 6 Kg.sq.cm
M.O.C: In M.S Duly Powder Coated
Two roll feeding system for Film
Motorized film unwinding system with geared motors
For top roll and bottom roll feeding
Dancing roller type sensing system
Timer based sealing, cooling and take off system
Power: 230V, 50Hz, 15 Amps
Sealing watts: 1.2 K.W X 1 No. (Front end)
Sealing Watts: 0.5 K.W X 2 Nos (Side sealing)
Rubber coated rollers with locking for film holding in top and bottom
Motorized conveyor in-feed system
Converised take off conveyor with sensors for adjustment
Approx Machine Dimension: 1800m (w) X 2400mm (H) X 3000mm (L)
Adjustable system for adjusting the sealing width

Shrink Tunnel

Model: SW-10060-H.D with Cooling Chamber

Chamber Size: 1000mm (W) x 600mm (H)
Hot Air Chamber Size: 1000mm (W) X 600mm (H) X 1200mm (L)
Cooling Chamber: 1000mm (W) X 600mm (H) X 400mm (L)
Machine Dimension: 1800mm (W) X 1400mm (H) X 2400mm (L)
Conveyor: Roller type conveyor duly coated
Roller will be coated with Silicon sleeves
Conveyor Drive: 1 H.P Variable Speed Drive, A.C variable speed drive
Digital type variable speed drive
Heavy Duty chains with pins for conveyor assembly.
Heater: 16 K.W Open type Porcelain heaters for better efficiency and Faster heating.
Digital Temperature controller with sensor to control the chamber temperature
With PID Controller system
Hot Air Blower: High velocity with 'F' class insulation, 1/2 H.P Cooling Fan: 200-Watts capacity x 3 Nos
Heavy Duty Gear box with the motor
Separate indicator for Input lines, Blower, Cooling fan, and Motor
Interlocking system between the controls for safety reasons.
Insulation: double class, Padded Glass Wool insulation for better heat insulation. Aluminum Heat resistant coating for the Hot Air Chamber.
M.O.C: In Mild Steel duly Powder Coated
Power: 440V, 50Hz, 3 Phase

Total Unit cost: Rs.12,00,000/-

Terms & Conditions:-

Prices: Ex-Works Chennai

Packing: Duly Stretch wrapped / In Wooden roadworthy cases, at extra cost depend upon the machine

Sales Tax:For Machines, Spare Parts/accessories – GST 18% applicable.

Transportation Freight: To pay basis, Transit Insurance at your interest

Installation/Commissioning: At Extra cost depending on the location to be installed.

Service Charges: Customer should bear all necessary travel, lodging, boarding charges of our Engineer as per estimate provided by us in advance.

Delivery: We shall be in a position to deliver the above machine within 6 - 8 weeks of receiving your confirmed order along with advance.

Guarantee/Warranty: Equipment supplied shall be Warranted against defective design, workmanship & material for a period of 12 months from date of supply. However this warranty does not cover damage due to accidents, mis-use or normal wear & tear & Warrantee shall be applicable only if we install equipment.

Payment: 50% advance of Basic Price along with confirmed order. **Balance 50%** along with taxes and duties, on proforma invoice basis, after inspection of the machine at our works prior to despatch of materials to site.

Trials: The purchaser should supply sufficient quantity of the Product and laminate free of cost, required for manufacturing and trials of the machine.

The Government Levis and transportation for the same shall be borne by the purchaser.

Validity: This offer is valid for 30 Days from the date of this offer.

Hope the details given above will be in line to your Requirements, and request you to place your valuable Orders with us.

With Warm Regards,
For **Taurean Pac, Chennai**

Leo Vinitha
9841696357