

GAURI PHARMA TECHNOLOGY

QUOTATION

DATED : 6/MAY/2023

QUOTATION NO.	GPT/04/2023/24
COMPANY NAME	VEDANTARAM
ADDRESS	HARIDWAR
CONTACT NO.	+919412074526
EMAIL	vedantaram1220@gmail.com
KIND ATTENTION	MR. NARESH CHAWLA JI
DESIGNATION	
CONTACT NO.	+919412074526
EMAIL ID	
REPRESENTATIVE	ANKIT SHARMA
CONTACT NO.	+91-8439105585,9027555585
EMAIL ID	gauripharma583@gmail.com
SUBJET	500 kg Ointment plant

COMMERCIAL PRICE

Please find below our offer for 500 kg Ointment/ Cream MFG. Plant

Sr. No.	Specification	Qty	Rate	Total
1.	Manufacturing Vessel with Anchor, homogenizer,hydraulic lifting	.		
2.	Wax Vessel with lose lid and small anchor Assygear box & 02 HP motor)	.		
3.	Vaccum Pump 3HP			
4.	Storage tank with loose lid 500 kg			
5.				
6.	Bump Pump model no 1 with 1 HP. motor SS coverand trolley			
7.	Control Panel			
	Grand Total			1400000.00

500 Kg Ointment Manufacturing Plant

	Specification
A) MANUFACTURING VESSEL	
WORKING CAPACITY	600 Ltrs.
GROSS CAPACITY	750 Ltrs.
TYPE	Conical I Bottom Type SS jacketed vessel with Top Dish Type
MOC	Vessel shell, Conical I bottom, from SS 316 quality SS Jacketed with insulation SS 304 Quality Material.
<u>MAIN VESSEL:</u>	<u>(SS 316 MATERIAL)</u>
INSIDE DIAMETER	I.D. 960 x 5 THK
INSIDE HEIGHT	712 mm
INSIDE THICKNESS	5 mm THK.
MATERIAL	SS 316 quality Material
TOP DISH & BOTTOM CONE	4 mm THK. (SS 316 quality)
<u>JACKET VESSEL</u>	<u>(SS MATERIAL)</u>
INSIDE DIAMETER	I.D. 1005 x 5 THK.
INSIDE HEIGHT	750 mm
INSIDE THICKNESS	4 mm THK
MATERIAL	SS 304 Quality Material
<u>INSULATION VESSEL</u>	<u>(SS 304 MATERIAL)</u>
INSIDE DIAMETER	I.D. 1055 x 2 THK.
INSIDE HEIGHT	280 mm
INSIDE THICKNESS	2 mm THK.
INSULATION	50 mm. thick with SS 304 2 mm THK. Sheet cover.
MATERIAL	SS 304 Quality Material
LEG PIPE	3 Nos. Heavy Duty leg pipe with base plate.
SHAFT	Heavy duty
AGITATOR	Anchor type agitator scrapper blade and side Teflon stripe

TOP DRY SEAL	Top dish side dry mechanical seal.(40mm Dia)
OUTLET	Ø 1.5" Flush bottom valve. (SS 316)
MOTOR	7.5HP, 1440 RPM, 415 V, 50 Hz with VFD
GEAR BOX	Bonfiglioli make.
ANCHOR RPM	35 RPM.MAXIMUM
TOP LID LIFTING	Hydraulic lifting arrangement with controller & power pack.
<u>HOMOGENIZER</u>	Bottom entry homogenizer 3 HP/2800 RPM, 415 V, 50 Hz with double cartridge mechanical seal water cooling system
SURFACES	All inside & outside mirror finish.
B) WAX PHASE VESSEL WITH TOP MOUNTED SMALL ANCHOR	
WORKING CAPACITY	75 Ltrs.
GROSS CAPACITY	100 Ltrs.
TYPE	Cylindrical vertical type SS Jacketed Vessel with bottom Dish end.
MOC	Vessel shell, bottom dish, Top loose Lid from SS 316 Quality SS Jacketed with Insulation SS 304 Quality Material.
<u>MAIN SHELL</u>	<u>(SS 316 MATERIAL)</u>
INSIDE DIAMETER	I.D. 800 x 4 THK.
INSIDE HEIGHT	725 mm
INSIDE THICKNESS	4mm THK.
MATERIAL	SS 316 Quality Material
TOP LOOSE LID	1.6 mm THK. (SS 316 Quality)
<u>JACKET VESSEL</u>	<u>(SS 304 MATERIAL)</u>
INSIDE DIAMETER	I.D. 800 x 4 THK.
INSIDE HEIGHT	560 mm
INSIDE THICKNESS	4 mm THK.
MATERIAL	SS Quality Material
<u>INSULATION VESSEL</u>	<u>(SS 304 MATERIAL)</u>
INSIDE DIAMETER	I.D. 860 x 1.6 THK.
INSIDE HEIGHT	560 mm
INSIDE THICKNESS	1.6 mm THK.
MATERIAL	SS 304 Quality Material
INSULATION	50 mm. thick with S.S. 16 SWG. Thick Sheet cover.

LEG PIPE	3 Nos. Heavy Duty leg pipe with base plate.
OUTLET	Ø 1.5" Flush bottom valve. (SS 316)
ANCHOR	SMALL ANCHOR
ANCHOR MOTOR	2 HP/1400 RPM three phase.
ANCHOR GEAR BOX	BONFIGLIOLI MAKE
SHAFT	Ø 30 Rod SS 316 Quality
SURFACES	All inside & outside mirror finish.

C) STORAGE TANK CONICAL TYPE: (GMPMODEL)

WORKING CAPACITY	625 Ltrs.
GROSS CAPACITY	700 Ltrs.
TYPE	Cylindrical vertical type with bottom cone end.
MOC	Vessel shell, bottom cone, Top loose Lid from SS 316 Quality
<u>MAIN VESSEL</u>	<u>(SS 316 MATERIAL)</u>
INSIDE DIAMETER	I.D. 850 x 1.6 THK.
INSIDE HEIGHT	750 mm
INSIDE THICKNESS	1.6 mm THK.
MATERIAL	SS 316 Quality Material
TOP LOOSE LID	1.6 mm THK. (SS 316 Quality)
LEG PIPE	3 Nos. leg pipes with PU Wheel
SURFACES	All inside & outside mirror finish.

D) ACCESSORY FOR OINTMENT PLANT:

1. VACUUM PUMP FOR VACUUM CREATE IN MANUFACTURING VESSEL 5 HP/2800 RPM (1 No.)
2. BUMP PUMP SS 316 QLTY. FOR CREAM TRANSFER 2 HP/350 RPM MOTOR (1 No.)
3. SS 316 QLTY. PIPE LINE WITH VALVES CONNECTED WITH 2 TANK CONNECTION T.C. TYPE..
4. ELECTRIC CONTROL PANEL WITH M.C.B. SWITCH FOR OINTMENT. MFG. PLANT.

TERMS & CONDITIONS:-

GST : ACTUAL 18%

DELIVERY : 6 to 8 Weeks from the date of acceptance

Advance.**PAYMENT** : 40% Advance, 60% Against

Performa Invoice. **TRANSPORT** : TO PAY

PACKING : Plastic wrap (If box packing required, packing charges extra to pay).

PACKING AND LOADING : 1 % OF TAX INVOICE.

VALIDITY : TWO WEEK

Insurance : The consignment will be insured at buyers cost if demanded.

We trust that you would find our offer quite in line with your requirement and most competitive. We look forward to receive your valued order, which will receive our prompt attention.

Thanks & Regards,

Ankit Sharma

MOBI- 09027555585,08439105585

EMAIL: gauripharma583@gmail.com

GST NO. 09CFXPS9572P1ZQ

Gauri Pharma Technology

Add. : Ward No. 9, 185 Khotihyate, Bulandshahr (U.P.) – 203001
Email Id : gauripharma583@gmail.com M.: 9027555585,8439105585

