Speed Post/Online

F. No.21-155/2017-IA-III Government of India Ministry of Environment, Forest and Climate Change (IA.III Section)

Indira Paryavaran Bhawan, Jor Bagh Road, New Delhi - 3

Date:

10th August, 2017

To,

M/s Prosper Buildtech Pvt. Ltd, 602 A, Plot No. 17, Sachdeva Corporate Tower, DDA Community Center, Kardardooma, Delhi-110092 Email: prosperbuildtech123@gmail.com

Subject: Group Housing Project at Plot No. Gh-4B, Sector-10, Greater Noida, Gautam Budh Nagar, Uttar Pradesh by M/s Prosper Buildtech Pvt. Ltd - Environmental Clearance - reg.

This has reference to your online proposal No. IA/UP/NCP/64499/2017 dated 5th May, 2017 submitted to this Ministry for grant of Environmental Clearance (EC) in terms of the provisions of the Environment Impact Assessment (EIA) Notification, 2006 under the Environment (Protection) Act, 1986.

- 2. The proposal for grant of environmental clearance to the project 'Group Housing Project at Plot No. Gh-4B, Sector-10, Greater Noida, Gautam Budh Nagar, Uttar Pradesh promoted by M/s Prosper Buildtech Pvt. Ltd was considered by the Expert Appraisal Committee (Infra-2) in its meeting held on 25th to 27th May, 2017. The details of the project, as per the documents submitted by the project proponent, and also as informed during the above meeting, are under:-
- (i) The present proposal is for development of a group housing project "Group Housing Project at Plot No. Gh-4B, Sector-10, Greater Noida, Gautam Budh Nagar, Uttar Pradesh promoted by M/s Prosper Buildtech Pvt. Ltd". Project site is spread over an area of 20240.00 sqm and and total built up area is 117575.43 sqm.
- (ii) Project involves construction of multi-storeyed residential with community facilities. Adequate parking 978 ECS is proposed on surface, stilt & basements for visitors as well as residents. Community facilities include club house, parks, and gardens. A total of 6651 sqm is to be developed as landscape area. The project envisages construction of 13 (11 Residential+ 2 facility blocks) of 2B+ST+22 floors. Total population of the proposed project will be 5127 which include the population of residents, community and visitors.
- (iii) Water requirement during construction phase will be 417 KLD. This includes domestic water requirement, flushing, D.G. cooling and landscaping. The total fresh water requirement is 282 KLD which includes domestic water requirement. The water requirement for flushing and landscaping will be met through treated water from STP.
- (iv) Wastewater generated during construction phase will be disposed-off in septic tanks/soak pit. It is expected that the project will generate approx.



- 326 KLD, which will be treated in onsite STP. The treated water will be recycled and re-used for flushing, D.G. cooling and landscaping.
- (v) Rainwater from the site will be collected and will be recharged into the ground through 5 nos. RWH pits. Capacity of each pit (RWH + de-silting chamber) is 6493.74 cum.
- (vi) Solid waste will be generated by the occupants of the residents, visitors and people coming to community area will pertain to the two categories, Bio-degradable and Non-biodegradable. It is estimated that maximum solid waste generation would be about 2.23 TPD for the proposed project and 117.4 kg of sludge will be generated from the proposed project.
- (vii) Power requirement during construction phase will be 2680 KW and In case of power failure, DG sets of total capacity of 2010 KVA (1x1010+2x500) for the proposed project will be provided as power back-up during construction phase.
- (viii) Total green area at the project site for both part A & part B is 6651 sq m, i.e. 32.86% of plot area.
- (ix) Parking space for 978 cars is available at the site. Parking will be provided in basements and stilts.
- (x) Cost of the project is Rs. 172.00 Crores
- (xi) **Employment potential:** It is estimated app. 150 workers will be employed during construction.
- (xii) **Benefits of the project:** During operational phase of Group Housing, persons will get employment opportunities as staff for management, maintenance and security. As an estimate, during operation phase, persons will get marginal employment opportunities from the residents of Group Housing who would work as domestic helpers. This will help in improving the quality of life of economically weaker sections of the local area.
- 3. The EAC, in its meeting held on 25th to 27th May, 2017, after detailed deliberations on the proposal, has recommended for grant of Environmental Clearance to the project. As per recommendations of the EAC, the Ministry of Environment, Forest and Climate Change hereby accords Environmental Clearance to the project 'Group Housing Project at Plot No. Gh-4B, Sector-10, Greater Noida, Gautam Budh Nagar, Uttar Pradesh promoted by M/s Prosper Buildtech Pvt. Ltd, under the provisions of the EIA Notification, 2006 and amendments/circulars issued thereon, and subject to the specific and general conditions as under:-

PART A - SPECIFIC CONDITIONS:

I. Construction Phase

- (i) The project proponent shall obtain all necessary clearance/ permission from all relevant agencies including town planning authority before commencement of work. All the construction shall be done in accordance with the local building byelaws.
- (ii) The natural drain system should be maintained for ensuring unrestricted flow of water. No construction shall be allowed to obstruct the natural drainage through the site, on wetland and water bodies. Check dams,

Page 2 of 8

- bio-swales, landscape, and other sustainable urban drainage systems (SUDS) are allowed for maintaining the drainage pattern and to harvest rain water. Buildings shall be designed to follow the natural topography as much as possible. Minimum cutting and filling should be done.
- Construction site shall be adequately barricaded before the construction begins. Dust, smoke & other air pollution prevention measures shall be provided for the building as well as the site. These measures shall include screens for the building under construction, continuous dust/ wind breaking walls all around the site (at least 3 meter height). Plastic/tarpaulin sheet covers shall be provided for vehicles bringing in dust pollution at the site as well as taking out debris from the site. Sand, murram, loose soil, cement, stored on site shall be covered adequately stone cutting. Unpaved surfaces and loose soil shall be adequately sprinkled with water to suppress dust.
- (iv) All construction and demolition debris shall be stored at the site (and not dumped on the roads or open spaces outside) before they are properly disposed. All demolition and construction waste shall be managed as per the provisions of the Construction and Demolition Waste Rules, 2016. All workers working at the construction site and involved in loading, unloading, carriage of construction material and construction debris or working in any area with dust pollution shall be provided with dust mask.
- (v) At least 20% of the open spaces as required by the local building byelaws shall be pervious. Use of Grass pavers, paver blocks with at least 50% opening, landscape etc. would be considered as pervious surface.
- (vi) Compliance with the Energy Conservation Building Code (ECBC) of Bureau of Energy Efficiency shall be ensured. Buildings in the States which have notified their own ECBC, shall comply with the State ECBC. Outdoor and common area lighting shall be LED. Concept of passive solar design that minimize energy consumption in buildings by using design elements, such as building orientation, landscaping, efficient building envelope, appropriate fenestration, increased day lighting design and thermal mass etc. shall be incorporated in the building design. Wall, window, and roof u-values shall be as per ECBC specifications.
- (vii) Use of water saving devices/ fixtures (viz. low flow flushing systems; use of low flow faucets tap aerators etc) for water conservation shall be incorporated in the building plan.
- (viii) Installation of dual pipe plumbing for supplying fresh water for drinking, cooking and bathing etc and other for supply of recycled water for flushing, landscape irrigation, car washing, thermal cooling, conditioning etc. shall be done.
- (ix) Separation of grey and black water should be done by the use of dual plumbing system. In case of single stack system separate recirculation lines for flushing by giving dual plumbing system be done.
- (x) Sewage shall be treated in the STP based on MBBR technology (with tertiary treatment i.e. Ultra Filtration). The treated effluent from STP shall be recycled/re-used for flushing, horticulture & DG cooling.

- (xi) The local bye-law provisions on rain water harvesting should be followed. If local bye-law provision is not available, adequate provision for storage and recharge should be followed as per the Ministry of Urban Development Model Building Byelaws, 2016. As proposed, 5 RWH tanks of total 5776.9 cum per year capacity shall be provided for storm water recharging to ground as per CGWB guidelines
- (xii) Separate wet and dry bins must be provided in each unit and at the ground level for facilitating segregation of waste. Solid waste shall be segregated into wet garbage and inert materials. Wet garbage shall be composted in Organic Waste Converter (OWC). As proposed, 125 m² of space shall be provided for OWC within the premises which will include area for segregation, composting. The inert waste from group housing project will be sent to dumping site.
- (xiii) Solar based electric power shall be provided to each unit for at least two bulbs/light and one fan. As proposed, central lighting and street lighting shall also be based on solar power.
- (xiv) A First Aid Room shall be provided in the project both during construction and operations of the project.
- (xv) Topsoil should be stripped to a depth of 20 cm from the areas proposed for buildings, roads, paved areas, and external services. It should be stockpiled appropriately in designated areas and reapplied during plantation of the proposed vegetation on site.
- (xvi) Disposal of muck during construction phase shall not create any adverse effect on the neighboring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- (xvii) The diesel generator sets to be used during construction phase shall be low sulphur diesel type and shall conform to Environmental (Protection) prescribed for air and noise emission standards.
- (xviii) Water demand during construction should be reduced by use of premixed concrete, curing agents and other best practices referred.
- (xix) As proposed, no ground water shall be used during construction/ operation phase of the project.
- (xx) Approval of the CGWA require before any dewatering for basements.
- (xxi) The approval of the Competent Authority shall be obtained for structural safety of buildings due to earthquakes, adequacy of firefighting equipment etc as per National Building Code including protection measures from lightening etc.
- (xxii) Any hazardous waste generated during construction phase, shall be disposed off as per applicable rules and norms with necessary approvals of the State Pollution Control Board.
- (xxiii) Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards be operated only during non-peak hours.
- (xxiv) An assessment of the cumulative impact of all activities being carried out or proposed to be carried out by the project, shall be made for traffic



densities and parking capabilities in a 05 kms. radius from the site. A detailed traffic management and a traffic decongestion plan drawn up through an organization of repute and specializing in Transport Planning shall be implemented to the satisfaction of the State Urban Development and Transport Departments shall also include the consent of all the concerned implementing agencies.

- (xxv) Ambient noise levels shall conform to residential standards both during day and night as per Noise Pollution (Control and Regulation) Rules, 2000. Incremental pollution loads on the ambient air and noise quality shall be closely monitored during construction phase. Adequate measures shall be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB / SPCB.
- (xxvi) Use of environment friendly materials in bricks, blocks and other construction materials, shall be required for at least 20% of the construction material quantity. These include Fly Ash bricks, hollow bricks, AACs, Fly Ash Lime Gypsum blocks, Compressed earth blocks, and other environment friendly materials. Fly ash should be used as building material in the construction as per the provision of Fly Ash Notification of September, 1999 and amended as on 27th August, 2003 and 25th January, 2016. Ready mixed concrete must be used in building construction.
- (xxvii) A comprehensive mobility plan, as per MoUD best practices guidelines (URDPFI), shall be prepared to include motorized, non-motorized, public, and private networks. Road should be designed with due consideration for environment, and safety of users. The road system can be designed
 - Hierarchy of roads with proper segregation of vehicular and pedestrian traffic.
 - Traffic calming measures
 - Proper design of entry and exit points.
 - Parking norms as per local regulation

II. Operational Phase

- (i) The gaseous emissions from DG set shall be dispersed through adequate stack height as per CPCB standards. Acoustic enclosure shall be provided to the DG sets to mitigate the noise pollution. Low sulphur diesel shall be used. The location of the DG set and exhaust pipe height shall be as per the provisions of the Central Pollution Control Board (CPCB) norms.
- For indoor air quality the ventilation provisions as per National Building (ii)
- Fresh water requirement from Municipal Water Supply shall not exceed (iii)
- The quantity of fresh water usage, water recycling and rainwater (iv) harvesting shall be measured and recorded to monitor the water balance as projected by the project proponent. The record shall be submitted to the Regional Office, MoEF&CC along with six monthly Monitoring reports.
- The installation of the Sewage Treatment Plant (STP) shall be certified by (V) an independent expert and a report in this regard shall be submitted to the Ministry before the project is commissioned for operation. Periodical,

- monitoring of water quality of treated sewage shall be conducted. Necessary measures should be made to mitigate the odour problem from STP.
- (vi) No sewage or untreated effluent water would be discharged through storm water drains.
- (vii) Sludge from the onsite sewage treatment, including septic tanks, shall be collected, conveyed and disposed as per the Ministry of Urban Development, Central Public Health and Environmental Engineering Organization (CPHEEO) Manual on Sewerage and Sewage Treatment Systems, 2013.
- (viii) The provisions of the Solid Waste (Management) Rules, 2016, e-Waste (Management) Rules, 2016, and the Plastics Waste (Management) Rules, 2016 shall be followed.
- (ix) Solar power shall be used for lighting in the apartment to reduce the power load on grid. Separate electric meter shall be installed for solar power. Solar water heaters shall be used to meet hot water demand, as far as possible.
- (x) Energy conservation measures like installation of CFLs/ LED for the lighting the area outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs, TFL and LED shall be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination.
- (xi) A minimum of 1 tree for every 80 sq.mt. of land should be planted and maintained. The existing trees will be counted for this purpose. Preference should be given to planting native species. Where the trees need to be cut, compensatory plantation in the ratio of 1:3 (i.e. planting of 3 trees for every 1 tree that is cut) shall be done and maintained. Area earmarked for greenbelt is 6651 sqm (approx. 32.86 % of Plot Area).
- (xii) The company will draw up and implement a Corporate Social Responsibility plan as per the Company's Act of 2013.
- (xiii) An environmental management plan (EMP) shall be prepared and implemented to ensure compliance with the environmental conditions specified above. A dedicated Environment Monitoring Cell with defined functions and responsibility shall be put in place to implement the EMP. The environmental cell shall ensure that the environment infrastructure like Sewage Treatment Plant, Landscaping, Rain Water Harvesting, Energy efficiency and conservation, water efficiency and conservation, solid waste management, renewable energy etc. are kept operational and meet the required standards. The environmental cell shall also keep the record of environment monitoring and those related to the environment infrastructure.

PART B - GENERAL CONDITIONS

(i) A copy of the environmental clearance letter shall also be displayed on the website of the concerned State Pollution Control Board. The EC letter shall

Page 6 of 8

- also be displayed at the Regional Office, District Industries centre and Collector's Office/ Tehsildar's office for 30 days.
- (ii) The funds earmarked for environmental protection measures shall be kept in separate account and shall not be diverted for other purpose. Year-wise Office.
- (iii) Officials from the Regional Office of MoEF&CC, Lucknow who would be monitoring the implementation of environmental safeguards should be given full cooperation, facilities and documents/data by the project proponents during their inspection. A complete set of all the documents submitted to MoEF&CC shall be forwarded to the APCCF, Regional Office of
 (iv) In the case of provide.
- (iv) In the case of any change(s) in the scope of the project, the project would require a fresh appraisal by this Ministry.
- (v) The Ministry reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.
- (vi) All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation (Protection) Act, 1972 etc. shall be obtained, as applicable by project proponents from the respective competent authorities.
- (vii) These stipulations would be enforced among others under the provisions of the Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention) Act, 1986, the Public Liability (Insurance) Act, 1991 and the (viii) The project prepenent about 1981 authorities.
- (viii) The project proponent shall advertise in at least two local Newspapers widely circulated in the region, one of which shall be in the vernacular language informing that the project has been accorded Environmental Clearance and copies of clearance letters are available with the State Pollution Control Board and may also be seen on the website of the Ministry of Environment, Forest and Climate Change at http://www.envfor.nic.in. The advertisement shall be made within Seven days from the date of receipt of the Clearance letter and a copy of the same shall be forwarded to the Regional Office of this Ministry at Lucknow.
- (ix) Any appeal against this clearance shall lie with the National Green Tribunal, the National Green Tribunal Act, 2010.
- (x) A copy of the clearance letter shall be sent by the proponent to concerned Panchayat, Zilla Parisad/Municipal Corporation, Urban Local Body and the Local NGO, if any, from whom suggestions/ representations, if any, were received while processing the proposal. The clearance letter shall also be put on the website of the company by the proponent.
- (xi) The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the

Page 7 of 8

Regional Office of MoEF&CC, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM, SO $_2$, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.

- (xii) The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall compliance of EC conditions and shall also be sent to the respective 4. This issues with the appropriate of the company along with the appropriate of the company along with the respective
- 4. This issues with the approval of the Competent Authority.

(Kushal Vashist) Director

Copy to:

- 1) The Secretary, Department of Environment, Government of Uttar Pradesh, Lucknow.
- The Addl. Principal Chief Conservator of Forests (C), Ministry of Environment, Forests and Climate Change, Kendriya Bhavan, 5th Floor, Sector-H, Aliganj, Lucknow-226024.
- The Chairman, Central Pollution Control Board Parivesh Bhavan, CBD-cum-Office Complex, East Arjun Nagar, New Delhi - 110 032.
- 4) Member Secretary, Uttar Pradesh Pollution Control Board, Building. No. TC-12V, Vibhuti Khand, Gomti Nagar, Lucknow-226 010
- 5) Monitoring Cell, MoEF&CC, Indira Paryavaran Bhavan, New Delhi.
- 6) Guard File/ Record File/ Notice Board.

(Kushal Vashist) Director