# STATE ENVIRONMENT IMPACT ASSESSMENT AUTHORITY HARYANA Bay No. 55-58, Prayatan Bhawan, Sector-2, PANCHKULA.

No. SEIAA/HR/2017/ 520

Dated:...31-07-2017.

To

M/S Emaar MGF Land Limited. Emaar MGF Business park, Mehrauli Gurgaon Road, Sikandarpur Chowk, Sector- 28, Gurgaon 122 002, Haryana.

## Subject: NangliUmarpur, Sector -62, Gurgaon, Haryana. Environmental Clearance for Group Housing colony located at village

Dear Sir,

procedure in the light of provisions under the EIA Notification, 2006 on the basis of the 31.08.2015; after its constitution. The proposal has been appraised as per prescribed above project under the EIA Notification, 2006. The proposal was transferred to MoEF & 31.08.2015, 13.02.2017 and 17.04.2017 seeking prior Environmental Clearance for the addressed to M.S. SEIAA, Haryana received on 04.11.2014 and subsequent letters dated response to the observations of the State Expert Appraisal Committee (SEAC) constituted Plan, EIA/EMP on the basis of approved TOR and additional clarifications furnished in mandatory documents enclosed with the application viz., Form-1, Form1-A, Conceptual by MOEF, GOI vide their Notification 21.08.2015, in its meetings held on 07.02.2015, grading to the project. GoI on 27.03.2015. No action was taken and the case was returned to SEIAA on 10.11.2016, 14.12.2016, 30.03.2017 This letter is in reference to your application no. nil dated 03.11.2014 and 29.05.2017 awarded "Gold"

located at village Nangli Umarpur, Sector -62, Gurgaon, Haryana as under: It is inter-alia, noted that the project involves the Group Housing colony

| 20 pits                                    | RWH               | 13.     |
|--|-------------------|---------|
| 1273 ECS (phase I- 748, phase-II -525)     | Parking           | 12.     |
| 431.862)                                   |                   |         |
| 1373.2 kg/day (phase I- 941.33, phase-II - | Solid Waste       | 11      |
| 1927 KW)                                   |                   |         |
| 5296 KW (Phase-I - 3369 KW & Phase-II-     | Power Requirement | 10.     |
| Phase I 170 KLD Phase II 80 KLD            | STP Capacity      | 9.      |
| Phase I 138 KLD + Phase II 63 KLD          | Waste Water       | 8.      |
| Phase I 106.44 KLD + Phase II 47.5 KLD     | Fresh Water       | 7.      |
| Phase I 208 KLD + Phase II 111 KLD         | Water requirement | 6.      |
| 30%  | Green belt        | 5.      |
| 100 Meter                                  | Height            | 4.      |
| center, club, service personals            |                   |         |
| Floors, convenient shopping, community     |                   |         |
| 6 Towers, 2 basement + GF + Maximum 28     | Nos. of Towers    | 3.      |
| 187514.31 sqm                              | Built up area     | 2.      |
| 56757.15sqm                                | Plot area         | 1.      |
| Remarks                                    | Particulars       | Sr. no. |
|  |                   |         |

mentioned below:-Notification 2006 subject to the strict compliance with the specific and general conditions accord necessary environmental clearance for the project under Category 8(b) of EIA meeting held on 24.07.2017 decided to agree with the recommendations of SEAC to conditions. Accordingly, the State Environment Impact Assessment Authority in its clearance for the project mentioned above, subject to compliance with the stipulated furnished in response to its observations, have recommended the grant of environmental the relevant documents submitted by the project proponent and additional clarification The State Expert Appraisal Committee, Haryana after due consideration of

#### PAKI A

## SPECIFIC CONDITIONS:

### Construction Phase:-

- $\Xi$ "Consent for Establish" shall be obtained from Haryana State Pollution Control Haryana before the start of any construction work at site Board under Air and Water Act and a copy shall be submitted to the SEIAA,
- [2] construction and operational phase of the project. A first aid room as proposed in the project report shall be provided both during
- wastes generated during the construction phase should be ensured. by the laboures workers at the site. Provision should be made for mobile toilets. Open defecation Adequate drinking water and sanitary facilities shall be provided for construction is strictly prohibited. The safe disposal of waste water and solid
- 4 horticulture/landscape development within the project site All the topsoil excavated during construction activities shall be stored for use in
- 2 of competent authority. general safety and health aspects of people, only in approved sites with the approval communities construction construction The project proponent shall ensure that the building material required during phase and should be disposed of after taking necessary precautions for waste should not create is properly stored within the project area and disposal of any adverse effect on the neighboring
- <u>[6]</u> any hazardous waste generated during construction phase, should be disposed off as Pollution Control Board per applicable rules and norms with necessary approval of the Haryana State material must be secured so that they should not leach into the ground water and must not be Construction spoils, including bituminous material and other hazardous materials, allowed to contaminate watercourses and the dump sites for such
- [7] The diesel generator sets to be used during construction phase shall be of ultra low prescribed for air and noise emission standards sulphur diesel type and should conform to Environment (Protection) Rules

- **[8**] if required, clearance from Chief Controller of Explosives shall be taken. The diesel required for operating DG sets shall be stored in underground tanks
- [9] closely monitored during construction phase. Adequate measures should be taken to Ambient noise levels shall conform to the residential standards both during day and conform to the stipulated residential standards of CPCB/MoEF. Incremental pollution loads on the ambient air and noise quality should ambient air pollution and noise level during construction phase, so as to
- [0]Fly ash shall be used as building material in the construction as per the provisions of Fly Ash Notification of September 1999 and as amended on 27th August 2003
- [11]applications should be ensured. Storm water control and its re-use as per CGWB and BIS standards for various
- [12] curing agents and other best practices. Water demand during construction shall be reduced by use of pre-mixed concrete
- [13] Roof must meet prescriptive requirement as per Energy Code by using appropriate thermal insulation material. Conservation
- [14] Opaque insulation material to fulfill requirement while it is desirable for non-air-conditioned spaces by use of appropriate thermal Building Code which is proposed to be mandatory for all air conditioned spaces wall must meet prescriptive requirement as per **Energy Conservation**
- [1**5**] The approval of the competent authority shall be obtained for structural safety of the National Building Code including protection measures from lightening etc. If any building on account of earthquake, adequacy of fire fighting equipments, etc. as per forest land is involved in the proposed site, clearance under Forest Conservation Act shall be obtained from the competent Authority.
- [16]removal of floating matter before entering harvesting pit. Maintenance budget and harvesting pits for recharging the ground water within the project premises. Rain The Project Proponent as stated in the proposal shall construct total 20 rain water that contaminated water do not enter any RWH pit. persons responsible for maintenance must be provided. Care shall also be taken water harvesting pits shall be designed to make provisions for silting chamber and
- [17]proponent shall take necessary permission regarding fire safety scheme/NOC by the local Authority/Directorate of fire from time to time. Further the project equipments as required by Haryana Fire Service Act, 2009 and instructions issued competent Authority as required. project proponent shall provide for adequate fire safety measures and
- [18]The Project Proponent shall obtain assurance from the DHBVN for supply of 5296 construction. In no case project will be operational solely on generators without power supply from any external power utility. (Phase-I - 3369 KW & Phase-II- 1927 KW) of power supply before the start of

- [19] Detail calculation of power load and ultimate power load of the project shall construction. Provisions shall be made for electrical infrastructure in the project DHBVN under intimation to SEIAA Haryana before the start
- [0]The Nallah/water course is not obstructed. depression / Nallah/water course and shall ensure that the natural flow from the Project Proponent shall not raise any construction Ħ. the natural land
- [21] The sufficiently above the level of the approach road to the Project. Levels of the other Project Proponent shall keep the plinth level of in the Projects shall also be kept suitably so as to avoid flooding the building blocks
- [22] norms approved by Director General Town and Country Department Haryana. Construction shall be carried out so that density of population does not
- [23] The Project Proponent shall submit an affidavit with the declaration that ground construction water will not be used for construction and only treated water should be used for
- [24]should be modified to include those trees in green area project proponent shall not cut any existing tree and project landscaping plan
- [25] project area, construction project dust screen for every floor above the proponent of stored shall provide material ð restrict dust and w meter high ground, proper sprinkling barricade air pollution around
- [26] project site to trap pollutant and other wastes during rains The project proponent shall construct a sedimentation basin in the lower level of the
- [27] strength for the project before the start of construction. project proponent shall provide proper rasta of proper width and proper
- [28] and maximum solar heat gain co-efficient is 0.25 for vertical fenestration project proponent shall ensure that the U-value of the glass is less than
- [29] Project Proponent shall provide respiratory protective equipment to all construction non-silica dust and wood dust. Such dusts shall not spread outside project premises The project proponent shall adequately control construction dusts like silica dust
- <u>[30]</u> The project proponent shall develop complete civic infrastructure of the Group possession of the units/flats thereafter. Housing colony including internal roads, green belt development, sewerage line, Water recharge arrangements, Storm water drainage system, Solid waste supply line, site and dual plumbing line, electric supply lines provision for treatment of bio-degradable waste, etc. and shall
- [31]The project proponent shall provide one refuge area till 24 meter, one till 39 and one after 15 meter each, as per National Building Code. The project proponent meter

- shall not convert any out/commercialized refuse area in the habitable space and it should not
- **[32]** above 30 meter as per National Building Code The project proponent shall provide fire control room and fire officer for building
- [33] for excavation of soil before the start of construction The project proponent shall obtain permission of Mines and Geology Department
- [34] other required services before taking up any construction activity. including their integration with external services of HUDA/ Local authorities beside Authority/HUDA regarding provision of storm drainage and sewerage project proponent shall seek specific prior approval from concerned system
- [35] detailed project for setting up the solid waste management plant shall be submitted The site for solid waste management plant be earmarked on the layout plan and the to the Authority within one month
- [36] Fire Department before the start of construction. The project proponent shall submit the copy of fire safety plan duly approved by
- [37] the public drainage system and shall seek permission of HUDA before the start of The project proponent shall discharge excess of treated waste water/storm
- 38 The project proponent shall maintain the distance between STP and water supply
- [39] highest tower project proponent shall ensure that the stack height S. 9 meter more than
- [40] of magnitude 8.5 on Richter scale The project proponent shall ensure that structural stability to withstand earthquake

#### Operational Phase:

- a Board under Air and Water Act and a copy shall be submitted to the SEIAA. Operate" shall be obtained from Haryana State Pollution
- Ξ treatment of waste water is mandatory. The project proponent shall remove not by an independent expert and a report in this regard shall be submitted to the recycled to achieve zero exit discharge. sewage to The Sewage Similarly total Nitrogen level shall be less than CPCB/ HSPCB, whichever is environmentally better. Project Proponent shall water. Discharge of treated sewage shall conform to the Ortho-Phosphorus but total Phosphorus to the extent of less than 2mg/liter. Haryana before the project is commissioned for operation. Tertiary Treatment Plant (STP) shall be installed for the treatment of the prescribed standards including odour and treated effluent will be The installation of STP 2mg/liter in tertiary treated waste norms and shall be certified standards of

implement such STP technology

which does not require filter

backwash.

equivalent to project proponent shall 50% of total capacity or as per the initial occupancy essentially provide two numbers of **STPs** as the case may preferably

- $\overline{\mathbf{c}}$ Separation of the grey and black water should be done by the use of dual plumbing to achieve zero exit discharge and the recycled water will be used for flushing, gardening and DG set cooling etc. ensuring that the re-circulated water should have BOD level less line. Treatment of 100% grey water by decentralized treatment should be than 5 mg/litre
- process should be used For disinfection of the treated wastewater ultra-violet radiation or ozonization
- [e]proponent with appropriate stack height above the highest roof level of the project common area illumination and for domestic use should be of enclosed type and location conform diesel (35 ppm sulphur), instead of low sulphur diesel. per the CPCB norms. The diesel used for DG sets shall be ultra low sulphur of the DG to rules generating made under the sets shall be sets proposed in the open as promised by the project Environment (Protection) Act, as source of back-up power for lifts 1986.
- $\Xi$ Housing Colony prescribed standards Ambient Noise level should be controlled to ensure that it does not exceed the both within and at the boundary of the Proposed Group
- <u>60</u> project and on the road sides preferably with local species which can provide as green cover area for tree plantation especially all around the periphery of the herbs & shrubs. Only locally available plant species shall be used protection against noise and suspended particulate matter. The open spaces inside project shall be project proponent as stated in the proposal should maintain at least 30% preferably fandscaped and covered with vegetation/grass
- **[h]** efficient irrigation minimizing grass area, using native variety, xeriscaping and mulching, utilizing The project proponent shall strive to minimize water in irrigation of landscape by system, scheduling irrigation only after checking evapo-

 $\Xi$ 

should be implemented. Rain water harvesting for roof run-off and surface run-off, as per plan submitted the highest ground water table. Care shall be taken that contaminated water do not through sedimentation tanks must be done to remove suspended matter, oil and material or paint which can contaminate rain water. Wire mess and filters should first 10 minutes enter any RWH The bore well for rainwater recharging shall be kept at least 5 mts. above pit. The project proponent shall avoid Rain Water Harvesting of rain fall. Roof top of the building shall be without any toxic Before recharging the surface run off, pre- treatment

used wherever required.

- consultation with Central Ground Water Authority ground water level and its quality should be monitored regularly Ħ.
- E details about building materials & technology, R & U Factors etc and submitted to norms finalized by Bureau of Energy Efficiency should be prepared incorporating the SEIAA, Haryana in three months time report on the energy conservation measures conforming to energy conservation
- outside the building and inside the building should be integral part of the project must be adapted to the maximum energy conservation. design and should be in place before project commissioning. Use of solar panels conservation measures like installation of LED only for lighting the areas
- $\Xi$ provide Halon free fire suppression system. insulation, refrigeration, air-conditioning and adhesive. Project Proponent shall also Proponent shall use zero ozone depleting potential material
- degradable waste should be treated by appropriate technology at the site ear-marked requirement of the MSW Rules, 2000 and as amended from time to time. The bio-The solid waste generated should be properly collected and segregated as per the approved sites for land filling after recovering recyclable material. within the project area and dry/inert solid waste should be disposed off to the
- HAREDA and shall be made operational in each building block. The provision of the solar water heating system shall be as per norms specified by
- internalized and no public space should be used requirement. There should be no traffic congestion near the entry and exit points adhered to traffic plan and the parking plan proposed by the Project Proponent should be the roads adjoining the proposed project site. Parking should be fully meticulously with further scope of additional parking for future
- [q] domestic water supply system in the area. Project shall be operationalized only when HUDA/local authority will provide
- I Operation and maintenance of STP, solid waste completion of project. pollution control measures shall be management and ensured even after
- S Different type of wastes should be disposed off as per provisions of municipal solid Management Rules 2001. The project proponent should maintain a collection center shall be disposed of as per existing E-waste Management Rules 2011 and Batteries under Environment Protection Act, 1986. Particularly E-waste and Battery waste waste, biomedical waste, hazardous waste, e-waste, batteries & plastic rules made and it shall be disposed of to only registered and authorized dismantler /

- schedules of rule 3 of Environment Protection Rule 1986 shall be strictly complied for discharge of environmental pollutants as enshrined Ħ.
- Water supply shall be metered among different users and different utilities
- ₹ 800 KVA shall be as per CPCB latest standards for high capacity DG sets. CPCB latest prescribed limits. Noise and Emission level of DG sets greater than tower and also ensure that the emission standards of noise and air are within the The project proponent shall ensure that the of DG sets is more than the highest
- **W** between 0.98 lag to 1 at the point of connection. All electric supply exceeding 100 amp, 3 phase shall maintain the power factor
- × power and water. Coil type cooling DG Sets shall be used for saving cooling water consumption for water cooled DG Sets Value and minimum outside fresh air supply may be resorted for conservation of best Co-efficient of Performance (Cop), as well as optimal Integrated Point Load summer and winter seasons should be kept at optimal level. Variable speed drive, use evaporative cooling technology and double stage cooling system for HVAC in project proponent for cooling, if it is at all needed. The Project Proponent shall also based HVAC system should be adopted and only treated water shall be used by project proponent shall not use fresh water for HVAC and DG cooling. Air reduce water consumption. Further temperature, relative humidity during
- $\mathbf{Y}$ project proponent shall obtain manufacturer's certificate also for that. quality grain oriented, low loss silicon steel and virgin electrolyte grade copper. The The project proponent shall ensure that the transformer is constructed with high
- $\mathbf{z}$ down-wash under any meteorological conditions sufficiently The project proponent shall ensure that exit velocity from the stack should high. Stack shall be designed in such a way that there
- [aa]The project proponent shall provide water sprinkling system in the project area to Air Environment Chapter of EMP suppress the dust in addition to the already suggested mitigation measures in the
- ab of Air Changes per hour/(ACH) in basement never falls below 15. In case of emergency capacity for increasing ACH to the extent of 30 must be provided by the basements area for comfortable living of human being and shall ensure that number The project proponent shall ensure proper Air Ventilation and light system in the
- [ac]prescribed standards till treated water supply is made available by HUDA proponent shall ensure drinking/ domestic water as
- [ad] The project proponent shall provide green area on terrace and roof top.
- [ae] The project proponent shall install solar panel for energy conservation

# PART-B. GENERAL CONDITIONS:

- Ξ commitment by project proponent. the most environmentally friendly commitment on the point shall be taken as and spirit. In case of contradiction between two or more documents on any point, environment and proposed environmental safeguards are complied with The Project Proponent shall ensure the commitments made in Form-1, Form-1A, other documents submitted to the SEIAA for the protection of
- Ξ MoEF HSPCB and SEIAA Haryana. (both in hard copies as well as by e-mail) to the northern Regional Office of compliance of the stipulated EC conditions including results of monitored project proponent shall also submit six monthly reports on the
- E environmental audit and shall take corrective measure, if required, without delay. Other environmental parameters and green belt shall be monitored on quarterly outlet after stabilization and stack emission shall be monitored monthly. After every ယ (three) months, the project proponent shall conduct
- Ĭ stipulated are not implemented to the satisfaction of SEIAA/MoEF this project. SEIAA reserves the right to revoke the clearance if conditions revoked if it is found that false information has been given for getting approval of The SEIAA, Haryana reserves the right to add additional safeguard measures found necessary. Environmental Clearance granted will be
- ⋖ The Project proponent shall not violate any judicial orders/pronouncements issued
- <u>₹</u> respective authorities prior to construction of the project. PLPA 1900, etc. shall be obtained, as applicable by project proponents from the Conservation Act, 1980 and Wildlife (Protection) Act, 1972, Forest Act, 1927, Controller of Explosives, Fire Department, Civil Aviation Department, All other statutory clearances such as the approvals for storage of diesel from Chief
- conditions shall also be put on project proponent's web site for public awareness advertised within 7 days from the date of issue of the clearance letter at least in two local newspapers that are widely circulated in the region and the copy of the same available with the Haryana State Pollution Control Board & SEIAA. This should be The Project proponent should inform the public that the project has been accorded Environment Clearance by the SEIAA and copies of the clearance forwarded to SEIAA Haryana. A copy of Environment Clearance
- [viii] project has been started before obtaining prior Environmental Clearance initiated against the Project Proponent if it was found that construction of the Under the provisions of Environment (Protection) Act, 1986, legal action shall be

- Section 16 of the National Green Tribunal Act, 2010. Any appeal against the this Environmental Clearance shall lie with the National Tribunal, if preferred, within a period of 30 days as prescribed
- $\blacksquare$ to SEIAA within 3 months of issuance of this letter. within 3 months period. Latest Corporate Environment Policy should be submitted mentioned in MoEF, GoI OM No. J-11013/41/2006-IA II (I) dated 26.4.2012 project proponent shall put in place Corporate Environment Policy as
- X. expenditure shall be reported to the SEIAA/RO MOEF GOI under rules prescribed for Environment Audit fund ear-marked account and should not be diverted for other purposes and year wise for environment protection measures should be kept in
- [iiix] The project proponent shall ensure the compliance of Forest Department, Haryana Notification no. S.O.121/PA2/1900/S.4/97 dated 28.11.1997.
- [XIII] The Project Proponent shall ensure that no vehicle during construction/operation certificate from competent Authority. enter the project premises without valid 'Pollution Under Control'
- [xiv] project proponent. himself /herself of the responsibility by shifting it to any contractor project proponent is Clearance letter responsible and project proponent can not absolve for compliance of all conditions engaged φ in
- VX is change in the planning of the proposed project. The project proponent shall seek fresh Environmental clearance if at any stage there
- [xvi] license/CLU Environmental Safeguards/ conditions imposed in the Besides the developer/applicant, the responsibility to ensure the compliance of shall also lie on the licensees has been granted by the Town & Country Planning Department, Ħ, Environmental whose name/names Clearance
- [xvii] Benzopyrine, arsenic and Nickel (Ambient levels as well as stack emissions) or the same periodically. It shall simultaneously be sent to the Regional Office of displayed at a convenient location near the main gate of the company in the public MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant critical levels namely; PM<sub>2.5</sub>, PM<sub>10</sub>, SO<sub>X</sub> NO<sub>X</sub>, Ozone, Lead, CO, Benzene, Ammonia, conditions, including results of monitored data on their website and shall proponent sectoral shall upload the status parameters, indicated for the project shall be monitored and of compliance of the stipulated EC
- [xviii] The environmental statement for each financial year ending 31st March in as is mandated to be submitted by the project proponent to the HSPCB Panchkula prescribed under the Environment (Protection) Rules, 1986, amended Form-V

subsequently, shall also be put on the website of the company along with the status Regional Offices of MoEF by e-mail. compliance of the EC conditions and shall also be sent to the respective

- The project proponent shall conduct environment audit at every three months Details of environmental audit and corrective measures shall be submitted in the interval and thereafter corrected measures shall be taken monitoring report. without any
- Corporate Environment and Social Responsibility (CSER) shall be laid down by the of its own choice and shall submit the same before the start of construction proponent shall select and prepare the list of the work for implementation of CSER executed under this responsibility shall be undertaken simultaneously. The project shall be submitted in the compliance. Environment related work proposed to be Corporate Affairs, GoI Notification Dated 27.02.2014. A separate audit statement Memorandum No. J-11013/41/2006-IA.II(I) dated 18.05.2012 and Ministry of project proponent (2% shall be earmarked) as per guidelines of MoEF, Gol Office
- welfare association/Housing co-operative societies shall responsible to comply The validity of this environment clearance letter is valid up to 7 years from the of the project. the laid down law of land. Compliance report should be sent to this office till life conditions laid down in EC. In case of violation the action would be taken as per life space project in case of Residential project will continue to apply. The resident date of issuance of EC letter. The environment clearance conditions applicable till

Member Secretary,
State Level Environment Impact
Assessment Authority, Haryana, Panchkula.

Endst. No. SEIAA/HR/2017/

Dated:...

A copy of the above is forwarded to the following:

- The Additional Director (IA Division), MoEF&CC, Bhavan, Zor bagh Road-New Delhi GoI, Indra
- 12 The Regional office, Ministry of Environment, Forests & Climate Change, Bay's no. 24-25, Sector 31-A, Dakshin Marg, Chandigarh
- ယ The Chairman, Haryana State Pollution Control Board, C-11, Sector-6, Pkl.

Member Secretary, State Level Environment Impact Assessment Authority, Haryana, Panchkula.