



## Karnataka State Pollution Control Board

**HEAD OFFICE :** "Parisara Bhavan",  
No.49, Church Street, Bengaluru-560001  
Tel No: 080-25589112/113, 080-25581383/388,  
Website: <https://kspcb.karnataka.gov.in>

**REGIONAL OFFICE :** Doddaballapura  
Urban Eco-park, 100 feet Road, Peenya Indl Area, IIIrd  
Phase, Bangalore -560058  
Tele : 080-28396000

### Consent For Operation(CFO-Air,Water) - (CfO-Fresh)

As per the provisions of  
The Water (Prevention & Control of Pollution) Act, 1974  
&  
The Air (Prevention & Control of Pollution) Act, 1981

To  
Fibroheal Woundcare Private Limited, Survey No.68 and 69, Varadanahalli  
village, Doddaballapur

for the Facility located at,  
Fibroheal Woundcare Private Limited, 68 and 69, Survey No.68 and 69,  
Varadanahalli village, Doddaballapur  
Bangalore Rural

Consent Order No	PCBID	INW ID	Industry Colour/Scale	Date of Issue
AW-128451	211799	279223	GREEN/SMALL	29/08/2024

This Consent is granted for the Products/ Activity/Service name indicated  
in the annexure along with the terms & conditions attached to this order

Validity through: 29/08/2024 to 31/12/2038



Combined Consent Order No: AW-128451

PCB ID: 211799

GSC No : PB0XG0000269223

Date: 29/08/2024

**Combined consent for discharge of effluents under the Water (Prevention and Control of Pollution) Act , 1974 and emission under Air (Prevention and Control of Pollution) Act , 1981**

Ref: 1. Application filed by the industry / organization on 07/08/2024  
2. Inspection of the Industry/organization/by RO, - Doddaballapura on 27/08/2024

Consent is hereby granted under Section 25(4) of the Water (Prevention & Control of Pollution) Act, 1974 ( herein referred to as the Water Act) & Section 21 of Air (Prevention & Control of Pollution) Act, 1981, ( herein referred to as the Air Act) and the Rules and Orders made there under and subject to the terms and conditions as detailed in the Schedule Annexed to this order.

The Occupier is authorized to operate /carryout industry/activity & to make discharge of the effluents & emissions confirming to the stipulated standards from the premises mentioned below:

**Location:**

Name of the Industry: Fibroheal Woundcare Private Limited  
Address: 68 and 69, , Survey No.68 and 69, Varadanahalli village, Doddaballapur  
Industrial Area: Doddaballapur I.A, Bangalore,  
Taluk: Dod Ballapur, District: Bangalore Rural

**Discharge of effluents under the Water Act:**

Sr	Water Code	WC(KLD)	WWG(KLD)	Remark
1	Domestic Purpose	1.300	0.900	Septic pit and Septic Tank
2	Manufacturing Processes	0.500	0.400	from vessel washing and it shall be utilized for onalnd for gardening

**Discharge of Air emissions under the Air Act from the following stacks etc.**

Sl. No. Description of chimney/outlet Limits specified refer schedule

The details of Sources, control equipments and its specification, type of fuel, rate of emissions, constituents to be controlled in emissions etc. are detailed in Annexure-I.

The consent for operation is granted considering the following activities/Products;

Sr	Product Name	Applied Qty	Unit
1	fibroheal surgical wound dressings	26000.0000	Number/month

This consent is valid for the period from 29/08/2024 to 31/12/2038

To,

Fibroheal Woundcare Private Limited  
Survey No.68 and 69, Varadanahalli  
village, Bashettihalli Gram Panchayat,  
Kasaba Hobli, Doddaballapur, Bangalore-  
561203.

**NOTE:**

The following Conditions Nil mentioned above are not applicable.

**COPY TO:**

1. Master Register.
2. Case file.

Consent Fee paid	: Rs. 60000
------------------	-------------

**SCHEDULE****TERMS AND CONDITIONS****A. TREATMENT AND DISPOSAL OF EFFLUENTS UNDER THE WATER ACT.**

1. The discharge from the premises of the occupier shall pass through the terminal manhole/manholes where from the Board shall be free to collect samples in accordance with the provisions of the Act/Rules made there under.
2. The sewage/domestic effluent shall be treated in septic tank and with soak pit. No overflow from the soak pit is allowed. The septic tank and soak pit shall be as per IS 2470 Part-I & Part-II.  
OR
3. The treated sewage effluent discharged shall conform to the standards specified in Annexure-I.
4. The occupier shall install flow measuring/recording devices to record the discharge quantity and maintain the record.
5. The occupier shall not change or alter either the quality or the quantity or the place of discharge or temperature or the point of discharge without the previous consent/ permission of the Board.
6. The Occupier shall not allow the discharge from the other premises to mix with the discharge from his premises. Storm water shall not be allowed to mix with the effluents on the upstream of the terminal manhole where the flow measuring devices are installed.
7. Domestic Sewage shall be discharged to Underground drainage System/ Sewers owned by Local body.

**B. EMISSIONS:**

1. The discharge of emissions from the premises of the applicant shall pass through the air pollution control equipment and discharged through stacks/chimneys mentioned in **Annexure-I** where from the Board shall be free to collect the samples at any time in accordance with the provisions of the Act and Rules made there under.
2. The occupier shall provide port holes for sampling of emission, access platforms for carrying out stack sampling, electrical points and all other necessary arrangements including ladder as indicated in Annexure-II.
3. The Occupier shall upgrade/modify/replace the control equipment with prior permission of the Board.

**C. MONITORING & REPORTING:**

1. The occupier shall get the samples of effluents & emissions collected and get them analyzed once a month for the parameters.



**D. SOLID WASTE (OTHER THAN HAZARDOUS WASTE) DISPOSAL:**

1. The Occupier shall segregate solid waste from Hazardous Waste, Municipal Solid Waste and store it properly till treatment/disposal without causing pollution to the surrounding Environment.
2. The solid waste generated shall be handled & disposed by scientific method without causing eye sore to the general public and to the surrounding environment.

**E. NOISE POLLUTION CONTROL:**

The applicant shall ensure that the ambient noise levels within its premises during construction and during operational period shall not exceed w.r.t Area/Zone as per Noise Pollution (Regulation and Control) Rules, 2000 as mentioned below:-

- a) In Industrial Area 75 dB(A) Leq during day time and 70 dB(A) Leq during night time.
- b) In Commercial Area 65 dB(A) Leq during day time and 55 dB(A) Leq during night time.
- c) In Residential Area 55 dB(A) Leq during day time and 45 dB(A) Leq during night time.
- d) In Silence Zone 50 dB(A) Leq during day time and 40 dB(A) Leq during night time.

Note: - \* Day time shall mean 6 am to 10 pm and Night time shall mean 10 pm to 6 am.

- \* dB(A) Leq denotes the time weighted average of the level of sound in decibels on scale A which is relatable to human hearing.
- \* A "decibel" is a unit in which noise is measured.
- \* "A", in dB(A) Leq, denotes the frequency weighting in the measurement of noise and corresponds to frequency response characteristics of the human ear.
- \* Leq: It is an energy mean of the noise level over a specified period.

**F. GENERAL CONDITIONS:**

1. The applicant shall obtain prior permission from the competent authority for drawing of water from Surface/Ground water source and submit a copy of the same to the Board.
2. The Board reserves the right to review, impose additional conditions, revoke, change or alter terms and conditions of this consent.
3. The Occupier shall forthwith keep the Board informed of any accidental discharge of emissions/effluents into the atmosphere in excess of the standards laid down by the Board. The applicant shall also take corrective steps to mitigate the impact.
4. The Occupier shall provide alternative power supply sufficient to operate all Pollution control equipments.

5. The entire premises shall always be kept clean. The effluent holding area, inspection chambers, outlets, flow measuring points should made easily approachable.
6. The Occupier shall display the consent granted in a prominent place for perusal of the inspecting officers of the Board.
7. The Occupier his heirs, legal representatives or assigns shall have no claims what so ever to the continuation or renewal of this consent after expiry of the validity of consent.
8. The Occupier shall make an application for consent at least 120 days before expiry of this consent.
9. The occupier shall maintain register recording the ambient air quality and stack monitoring. The register shall be open for inspection by the Board Officers at all time.

#### Annexure-I

S/no	Characteristics	Tolerance Limits
1	Colour and Odour	See Note
2	Suspended Solids, mg/l.max	30
3	Bio-chemical Oxygen Demand, mg/l, max ( 3 days at 27 deg/Centigrade)	20

**Note:** All efforts should be made to remove colour and unpleasant odour as far as practicable.

#### Annexure-II

Chim. No.	Chimney attached to	KVA Rating/ Capacity	Minimum chimney height to be provided above ground level (in Mtr)	Constituents to be controlled in the emission	Tolerance limits mg/NM3	Air pollution Control equipment to be installed,in addition to chimney height as per col.(4)	Date on which air pollution control equipments shall be provided to achieve the stipulated tolerance limits and chimney heights conforming to stipulated heights.
1	D.G. Sets	62.5 kVA		5 PM,SO <sub>2</sub> ,NO <sub>x</sub>	---	AEC	---
2	D.G. Sets	200 KVA		5 PM,SO <sub>2</sub> ,NO <sub>x</sub>	---	AEC	---
3	Any Other.....	Air Handling system		1 PM,SO <sub>2</sub> ,NO <sub>x</sub>	0,0,0,0,0	FIL	---

Note:

AEC : Accoustic Enclosures

FIL : Bag Filter



**Note:**

1. The DG set shall be provided with acoustic measures as per SI.No.94 in Schedule-I of Environment (Protection) Rules.
2. There shall be no smell or odour nuisance from the industry.

**LOCATION OF SAMPLING PORTHOLE, THE PLATFORMS, THE ELECTRICAL OUTLET.**

1. Location of Portholes and approach platform:

Portholes shall be provided for all chimneys, stacks and other sources of emission. These shall serve as the sampling points. The sampling point should be located at a distance equal to atleast eight times the stack or duct diameters downstream and two diameters upstream from source of low disturbance such as a Bend, Expansion, Construction Valve, Fitting or Visible Flame for rectangular stacks, the equivalent diameter can be calculated from the following equation.

$$\text{Equivalent Diameter} = \frac{2 (\text{Length} \times \text{Width})}{(\text{Length} + \text{Width})}$$

2. The diameter of the sampling port should not be less than 3". Arrangements should be made so that the porthole is closed firmly during the period when it is not used for sampling.
3. An easily accessible platform to accommodate 3 to 4 persons to conveniently monitor the stack emission from the portholes shall be provided. Arrangements for an Electric Outlet Point off 230 V 15 A with suitable switch control and 3 Pin Point shall be provided at the Porthole location.

For and on behalf of  
Karnataka State Pollution Control Board

*Signature Not Verified*

*Digitally signed by*

*Date: 2024.08.29 13:49:14*

*+05:30*